

Version 02. Supersedes version: 01

Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

VM-EA 300 Comp. A

Article number: 0911005300A

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Adhesive mortar for fastening to concrete elements A-Component (Resin)

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Kellner & Kunz AG

Boschstr. 37 4600 Wels / AUSTRIA Phone 0043-7242-484-0 Fax 0043-7242-484-924 Homepage www.reca.co.at E-mail info@reca.co.at

Address enquiries to

Technical information info@reca.co.at
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +43 (0) 1 406 43 43 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Skin Sens. 1: H317 May cause an allergic skin reaction. Eye Irrit. 2: H319 Causes serious eye irritation.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

Signal word WARNING

Contains: Tetramethylene dimethacrylate

Ethylene dimethacrylate

Methacrylic acid, monoester with Propan-1,2-diole

2,2'-[(4-methylphenyl)imino]bisethanol

Hazard statements H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection / face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention. P337+P313 If eye irritation persists: Get medical advice / attention. P362+P364 Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

Environmental hazardsDoes not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.



SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

| Range [%] | Substance |
|-----------|---|
| | |
| | Tetramethylene dimethacrylate |
| | CAS: 2082-81-7, EINECS/ELINCS: 218-218-1, Reg-No.: 01-2119967415-30-XXXX |
| | GHS/CLP: Skin Sens. 1B: H317 |
| 1 - <10 | Vinyltoluene |
| | CAS: 25013-15-4, EINECS/ELINCS: 246-562-2, Reg-No.: 01-2119622074-50-XXXX |
| | GHS/CLP: Flam. Liq. 3: H226 - Acute Tox. 4: H332 - Eye Irrit. 2: H319 - Skin Irrit. 2: H315 - Asp. Tox. 1: H304 - Aquatic Chronic 3: H412 |
| 1 - <5 | Ethylene dimethacrylate |
| | CAS: 97-90-5, EINECS/ELINCS: 202-617-2, EU-INDEX: 607-114-00-5, Reg-No.: 01-2119965172-38 |
| | GHS/CLP: STOT SE 3: H335 - Skin Sens. 1: H317 |
| 1 - <5 | Methacrylic acid, monoester with Propan-1,2-diole |
| | CAS: 27813-02-1, EINECS/ELINCS: 248-666-3, Reg-No.: 01-2119490226-37-XXXX |
| | GHS/CLP: Eye Irrit. 2: H319 - Skin Sens. 1: H317 |
| 1 - <3 | 2,2'-[(4-methylphenyl)imino]bisethanol |
| | CAS: 3077-12-1, EINECS/ELINCS: 221-359-1, Reg-No.: 01-2120791684-40-XXXX |
| | GHS/CLP: Acute Tox. 4: H302 - Skin Sens. 1: H317 - Eye Dam. 1: H318 - Aquatic Chronic 3: H412 |
| 0,1 - <1 | 1,1'-(p-Tolylimino)dipropan-2-ol |
| | CAS: 38668-48-3, EINECS/ELINCS: 254-075-1, Reg-No.: 01-2119980937-17-XXXX |
| | GHS/CLP: Acute Tox. 2: H300 - Eye Irrit. 2: H319 - Aquatic Chronic 3: H412 |
| 0,1 - <1 | 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate |
| | CAS: 6846-50-0, EINECS/ELINCS: 229-934-9, Reg-No.: 01-2119451093-47-XXXX |
| | GHS/CLP: Repr. 2: H361 - Aquatic Chronic 3: H412 |

Comment on component parts The quartz in this preparation is not available on foreseeable use.

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



Date printed 21.11.2019, Revision 20.11.2019 Version 02. Supersedes version: 01 Page 3 / 13

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released:

Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.

Take up residues with absorbent material (e.g. sand, sawdust, general purpose binder,

diatomaceous earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.

Avoid contact with eyes and skin. Use personal protective equipment.

Open and handle container with care.

Do not eat, drink, smoke or take drugs at work.

Wash hands before breaks and after work

Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container in a well-ventilated place.

Keep container tightly closed.

Keep in a cool place. Store in a dry place. Protect from atmospheric moisture and water.

Recommended storage temperature: 5-25 °C (41-77 °F).

7.3 Specific end use(s)

See product use, SECTION 1.2



Date printed 21.11.2019, Revision 20.11.2019

Version 02. Supersedes version: 01

Page 4 / 13

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Vinyltoluene

CAS: 25013-15-4, EINECS/ELINCS: 246-562-2, Reg-No.: 01-2119622074-50-XXXX

Long-term exposure: 100 ppm, 491 mg/m³

Short-term exposure (15-minute): 150 ppm, 736 mg/m³

DNEL

| Substance |
|---|
| Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1 |
| Industrial, inhalative, Long-term - systemic effects: 264.5 mg/m³. |
| Industrial, dermal, Long-term - systemic effects: 4.2 mg/kg bw/day. |
| general population, oral, Long-term - systemic effects: 2.5 mg/kg bw/day. |
| general population, dermal, Long-term - systemic effects: 2.5 mg/kg bw/day. |
| general population, inhalative, Long-term - systemic effects: 8.8 mg/m³. |
| Tetramethylene dimethacrylate, CAS: 2082-81-7 |
| Industrial, dermal, Long-term - systemic effects: 4.2 mg/kg bw/day. |
| Industrial, inhalative, Long-term - systemic effects: 14.5 mg/m³. |
| general population, oral, Long-term - systemic effects: 2.5 mg/kg bw/day. |
| general population, dermal, Long-term - systemic effects: 2.5 mg/kg bw/day. |
| general population, inhalative, Long-term - systemic effects: 4.3 mg/m³. |
| 1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3 |
| Industrial, inhalative, Long-term - systemic effects: 2,47 mg/m³. |
| Industrial, dermal, Long-term - systemic effects: 700 μg/kg bw/day. |
| general population, oral, Long-term - systemic effects: 250 μg/kg bw/day. |
| Ethylene dimethacrylate, CAS: 97-90-5 |
| Industrial, dermal, Long-term - systemic effects: 1,3 mg/kg bw/d. |
| Industrial, inhalative, Long-term - systemic effects: 2,45 mg/m³. |
| general population, dermal, Long-term - systemic effects: 100 mg/kg bw/d. |
| general population, oral, Long-term - systemic effects: 100 mg/kg bw/d. |
| general population, inhalative, Long-term - systemic effects: 1,47 mg/m³. |
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate, CAS: 6846-50-0 |
| Industrial, dermal, Long-term - systemic effects: 5 mg/kg bw/day. |
| Industrial, inhalative, Long-term - systemic effects: 17,62 mg/m³. |
| general population, inhalative, Long-term - systemic effects: 4,35 mg/m³. |
| general population, dermal, Long-term - systemic effects: 5 mg/kg bw/day. |
| general population, oral, Long-term - systemic effects: 5 mg/kg bw/day. |
| 2,2'-[(4-methylphenyl)imino]bisethanol, CAS: 3077-12-1 |
| Industrial, dermal, Long-term - systemic effects: 470 μg/kg bw/day. |
| Industrial, inhalative, Long-term - systemic effects: 3,29 mg/m³. |
| general population, inhalative, Long-term - systemic effects: 580 μg/m³. |
| general population, oral, Long-term - systemic effects: 160 μg/kg bw/day. |
| general population, dermal, Long-term - systemic effects: 170 μg/kg bw/day. |
| |
| |

PNEC

Substance



Page 5 / 13

Version 02. Supersedes version: 01

Date printed 21.11.2019, Revision 20.11.2019

| Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1 | | |
|--|--|--|
| seawater, 0.904 mg/L. | | |
| sewage treatment plants (STP), 10 mg/L. | | |
| sediment (freshwater), 6.28 mg/kg. | | |
| sediment (seawater), 6.28 mg/kg. | | |
| freshwater, 0.904 mg/L. | | |
| soil, 0.727 mg/kg. | | |
| Tetramethylene dimethacrylate, CAS: 2082-81-7 | | |
| soil, 0.573 mg/kg. | | |
| sediment (seawater), 0.312 mg/kg. | | |
| sediment (freshwater), 3.12 mg/kg. | | |
| sewage treatment plants (STP), 2 mg/L. | | |
| seawater, 0.004 mg/L. | | |
| freshwater, 0.043 mg/L. | | |
| 1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3 | | |
| seawater, 0,0017 mg/l. | | |
| sediment (seawater), 16,3 µg/kg sediment dw. | | |
| sediment (freshwater), 163 µg/kg sediment dw. | | |
| soil, 22,6 µg/kg soil dw. | | |
| sewage treatment plants (STP), 199,5 mg/l. | | |
| freshwater, 0,017 mg/l. | | |
| Ethylene dimethacrylate, CAS: 97-90-5 | | |
| soil, 239 µg/kg dw. | | |
| sediment (seawater), 0,16 mg/kg dw. | | |
| sediment (freshwater), 1,6 mg/kg dw. | | |
| sewage treatment plants (STP), 57 mg/l. | | |
| seawater, 13,9 µg/l. | | |
| freshwater, 139 µg/l. | | |
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate, CAS: 6846-50-0 | | |
| sediment (seawater), 529 µg/kg sediment dw. | | |
| freshwater, 0,014 mg/l. | | |
| seawater, 0,0014 mg/l. | | |
| sewage treatment plants (STP), 3 mg/l. | | |
| sediment (freshwater), 5,29 mg/kg sediment dw. | | |
| 2,2'-[(4-methylphenyl)imino]bisethanol, CAS: 3077-12-1 | | |
| sewage treatment plants (STP), 10 mg/L. | | |
| sediment (freshwater), 121,4 μg/kg sediment dw. | | |
| freshwater, 26,4 µg/L. | | |
| seawater, 2,64 µg/L. | | |

soil, 8,8 µg/kg soil dw.

sediment (seawater), 12,1 µg/kg sediment dw.



Date printed 21.11.2019, Revision 20.11.2019 Version 02. Supersedes version: 01 Page 6 / 13

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance

requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection safety glasses (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

>0,2 mm Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protectionProtective clothing (EN 340)OtherAvoid contact with eyes and skin.

Do not inhale gases/vapours/aerosols.

Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)

Thermal hazards not applicable

Delimitation and monitoring of the environmental exposition

Protect the environment by applying appropriate control measures to prevent or limit

emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form pasty

Color light beige

Odor characteristic

Odour threshold No information available.

pH-value not applicablepH-value [1%] not applicable

Boiling point [°C] No information available.

Flash point [°C] >65

Flammability (solid, gas) [°C] not applicable

Lower explosion limit not determined

Upper explosion limit not determined

Oxidising properties none

Vapour pressure/gas pressure [kPa] No information available.

Density [g/ml] 1,72

Bulk density [kg/m³] not applicable
Solubility in water insoluble

Partition coefficient [n-octanol/water] No information available.

Viscosity No information available.

Relative vapour density determined No information available.

in air
Evaporation speed

Melting point [°C]

No information available.

No information available.

Autoignition temperature [°C] not self-igniting

Decomposition temperature [°C] No information available.

9.2 Other information

No information available.



Date printed 21.11.2019, Revision 20.11.2019

Version 02. Supersedes version: 01

Page 7 / 13

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with oxidizing agents. Reactions with acids.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Version 02. Supersedes version: 01 Page 8 / 13

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product ATE-mix, oral, > 2000 mg/kg. ATE-mix, dermal, > 2000 mg/kg. ATE-mix, inhalation (vapour), > 20 mg/l.

Substance

Vinyltoluene, CAS: 25013-15-4

LD50, oral, Rat: 4000 mg/kg (IUCLID)

LC50, inhalative, Rat: 2500 ppm/8h (IUCLID).

LC50, inhalative, mouse: 3,02 mg/l/4h (IUCLID)

Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1

LD50, oral, Rat: 11200 mg/kg.

LD50, dermal, Rabbit: > 5000 mg/kg.

Tetramethylene dimethacrylate, CAS: 2082-81-7

LD50, oral, Rat: > 5000 mg/kg OECD 401.

LD50, dermal, Rabbit: > 3000 mg/kg

1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3

LD50, dermal, Rat: >2000 mg/kg.

LD50, oral, Rat: 25 - 200 mg/kg.

Ethylene dimethacrylate, CAS: 97-90-5

LD50, oral, Rat: 8300 mL/kg bw.

LD50, dermal, Rat: > 2000 mg/kg bw.

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate, CAS: 6846-50-0

LD50, oral, Rat: > 3200 mg/kg.

LD50, dermal, Rabbit: 18900 mg/kg.

LC50, inhalative, Rat: 5,3 mg/l/6h.

2,2'-[(4-methylphenyl)imino]bisethanol, CAS: 3077-12-1

LD50, dermal, Rat: >2000 mg/kg bw.

LD50, oral, Rat: 959 mg/kg bw.

Serious eye damage/irritation Irritant

Calculation method

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Calculation method

Respiratory or skin sensitisation May cause an allergic skin reaction.

Calculation method

Specific target organ toxicity -

single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — Based on the available information, the classification criteria are not fulfilled.

repeated exposure

Mutagenicity Based on the available information, the classification criteria are not fulfilled. Reproduction toxicity Based on the available information, the classification criteria are not fulfilled. Carcinogenicity Based on the available information, the classification criteria are not fulfilled. Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.



Date printed 21.11.2019, Revision 20.11.2019 Version 02. Supersedes version: 01

Page 9 / 13

SECTION 12: Ecological information

12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled.:

Substance

Vinyltoluene, CAS: 25013-15-4

LC50, (96h), Pimephales promelas: 23,4 mg/l (IUCLID).

Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1

LC50, (48h), Leuciscus idus: 493 mg/l (DIN 38412).

EC50, (48h), Daphnia magna: 380 mg/l (OECD 202).

EC50, (72h), Pseudokirchneriella subcapitata: 97,2 mg/l (OECD 201).

Tetramethylene dimethacrylate, CAS: 2082-81-7

LC50, (48h), Leuciscus idus: 32,5 mg/l DIN 38412.

EC10, (16h), Pseudomonas putida: > 1000 mg/l.

1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3

LC50, (96h), fish: 17 mg/l.

EC50, (72h), Algae: 245 mg/l.

EC50, (48h), Daphnia magna: 28,8 mg/l.

Ethylene dimethacrylate, CAS: 97-90-5

LC50, (96h), Danio rerio: 15,95 mg/l (OECD 203).

EC50, (48h), Daphnia magna: 44,9 mg/l.

EC50, (72h), Algae: 17,3 mg/l

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate, CAS: 6846-50-0

LC50, (96h), Pimephales promelas: 1,55 mg/l.

EC50, (48h), Daphnia magna: 1,46 mg/l.

EC50, (72h), Algae: 7,49 mg/L

2,2'-[(4-methylphenyl)imino]bisethanol, CAS: 3077-12-1

LC50, (96h), fish: 100 mg/L

EC50, (48h), Invertebrates: 26.4 mg/L

EC50, (72h), Algae: 100 mg/L.

12.2 Persistence and degradability

Behaviour in environment

No information available.

compartments

No information available.

Behaviour in sewage plant Biological degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.



Version 02. Supersedes version: 01

Page 10 / 13

12.6 Other adverse effects

Do not discharge product unmonitored into the environment.

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

150110* Waste no. (recommended)

150102

SECTION 14: Transport information

14.1 UN number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable



Date printed 21.11.2019, Revision 20.11.2019

Version 02. Supersedes version: 01

Page 11 / 13

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

IMDG

not applicable

no

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

Inland navigation (ADN) no

Marine transport in accordance with

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008;

75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) 2,8%

15.2 Chemical safety assessment

not applicable



Version 02. Supersedes version: 01

Page 12 / 13

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H361 Suspected of damaging fertility or the unborn child.

H300 Fatal if swallowed.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

H412 Harmful to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H226 Flammable liquid and vapour.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises

dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par

voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived Willimum Ellect E

DNEL = Derived No Effect Level

EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform Chemical Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method) Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)



Version 02. Supersedes version: 01

Page 13 / 13

Modified position

SECTION 3 deleted: Ethylene dimethacrylate

SECTION 3 deleted: 2,2'-[(4-methylphenyl)imino]bisethanol

SECTION 3 deleted: 1,4-naphthoquinone

SECTION 3 been added: Ethylene dimethacrylate

SECTION 3 been added: 2,2'-[(4-methylphenyl)imino]bisethanol

SECTION 3 been added: 1,1'-(p-Tolylimino)dipropan-2-ol

SECTION 3 been added: 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

SECTION 2 been added: 2,2'-[(4-methylphenyl)imino]bisethanol

SECTION 3 deleted: 1,1'-(p-Tolylimino)dipropan-2-ol SECTION 2 deleted: H315 Causes skin irritation.

SECTION 2 deleted: Skin Irrit. 2

SECTION 2 deleted: Aquatic Chronic 3

SECTION 2 deleted: H412 Harmful to aquatic life with long lasting effects.

SECTION 2 deleted: P273 Avoid release to the environment.

SECTION 4 been added: Do not induce vomiting.

SECTION 8 deleted: If ventilation is insufficient, wear respiratory protection.

SECTION 8 been added: In the event of occupational exposure limits being exceeded or of

inadequate ventilation: wear appropriate respiratory protection. SECTION 8 deleted: Nitrile rubber, >480 min (EN 374-1/-2/-3).

SECTION 11 deleted: Irritant

SECTION 11 been added: Based on the available information, the classification criteria are

not fulfilled.

SECTION 16 deleted:

SECTION 16 deleted: Calculation method SECTION 16 deleted: Calculation method SECTION 16 deleted: Calculation method

Copyright: Chemiebüro®